



---

# CSE101-Lec#25-26-27

---

## Array and Pointers

**Created By:**  
**Amanpreet Kaur &**  
**Sanjeev Kumar**  
**SME (CSE) LPU**



# Outline

- Pointer to Array
- Pointer to group of 1D arrays
- Array of pointers.



# (lec-25)Pointer to Array

- Array name itself is an address or pointer. It points to the first element(0<sup>th</sup> element) of array.
- The arrays are accessed by pointers in same way as we access arrays using array name.
- Consider an array `b[5]` and a pointer `bPtr` :
  - `bPtr[3]` is same as `b[3]`

Program to find the mean of array using array name as a pointer.

```
#include<stdio.h>
#include<conio.h>
void main()
{
int a[] = {3, 7, -1, 4, 6};
int i;
double mean = 0;//compute mean of values in a
for (i = 0; i < 5; ++i)
{
mean += *(a + i);
}
mean /= 5;
printf("Mean = %.2f\n", mean);
getch();
}
```

Program to find  
the mean of  
array using  
pointer to array.

```
#include<stdio.h>
#include<conio.h>
void main()
{
int a[] = {3, 7, -1, 4, 6};
int i;
int *aptr = a;
double mean = 0;//compute mean of values in a
for (i = 0; i < 5; ++i)
{
mean += *(aptr + i);
}
mean /= 5;
printf("Mean = %.2f\n", mean);
getch();
}
```



# Practice Session

- Practice various programs of arrays and same program by using pointer to array.
  - Example program:
    - Find sum of squares and sum of cubes of array elements using pointers.
    - To copy elements of one array to another using pointer to array.
    - To find the maximum value out of the array elements.
    - All the operations possible on arrays.

# (Lec-26) Pointer to group of 1D Arrays

- 1-D array can be represented in terms of a pointer (array name) and an subscript,
- 2-D array can also be represented with an equivalent pointer notation.
- A 2-D array is actually a collection of 1-D arrays.
- Therefore , **we can define a 2-D array as a pointer to a group of contiguous 1-D arrays.**
- 2 D array declaration can be written as

`data-type (*ptrvar) [expression 2];`

rather than

`data type array[expression 1] [expression 2];`



- Eg: `myArray` is 2 D array having 10 rows and 20 columns. The item in row 2 and column 5 can be accessed by writing:

```
myArray[2][5];
```

or

```
*(*myArray+2)+5)
```



- `myArray` is a 2 D array having 10 rows and 20 columns. We can declare x as:

```
int (*myArray) [20];
```

Rather than

```
int myArray[10] [20];
```

- In this first declaration, `myArray` is defined to be a pointer to a group of contiguous 1 –D 20 element integer arrays.
- Thus `myArray` points to the first 20 element array which is actually the first row i.e row 0 of original 2 D array.
- Similarly, `(myArray+1)` points to the second 20 element array and so on.



# Arrays of Pointers

- We can have arrays of pointers since pointers are variables.
- An array of pointers is a collection of **addresses**.
- A common use of an **array of pointers** is to form an **array of strings**, referred to simply as a **string array**.
- Each entry in the array is a string, but in C a string is essentially a pointer to its first character.
- So each entry in an array of strings is actually a pointer to the first character of a string.

# Arrays of Pointers

The `suit[4]` portion of the definition indicates an array of 4 elements.


- **Example:**

```
const char *suit[ 4 ] = {"Hearts", "Diamonds",  
"Clubs", "Spades" };
```

The `char *` portion of the declaration indicates that each element of array `suit` is of type "pointer to char."

# Arrays of Pointers

- `char *` indicates that each element of `suit` is a “pointer to a `char`”
- The strings are not actually stored in the array `suit`, only pointers to the strings are stored



`suit` array has a fixed size, but strings can be of any size



# Arrays of Pointers

- The four strings are 7, 9, 6 and 7 characters long, respectively.
- Although it appears as though these strings are being placed in the suit array, only pointers are actually stored in the array
- Each pointer points to the first character of its corresponding string.
- Thus, even though the suit array is fixed in size, it provides access to character strings of any length.

# Program to show array of pointers.

```
#include<stdio.h>
void main()
{
    int i;
    char *suit[4]={"spades","hearts","clubs",
"diamonds"};
    printf("The suit of cards have:");
    for(i=0; i<4; i++){
        printf("%s\n",suit[i]);
    }
}
```

The suit of cards have:  
spades  
hearts  
clubs  
diamonds



- However pointers and arrays are different:
- A pointer is a variable. We can do  
     $pa = a$  and  $pa++$ .
- An Array **is not** a variable.  
     $a = pa$  and  $a++$  **ARE ILLEGAL**



# Practice session

- Practice various programs in detail in class on array of pointers.
  - Example program
    - To store address of different elements of an array.
    - To display address of elements and address of pointers.





---

# Next Class: Dynamic Memory Management

[cse101@lpu.co.in](mailto:cse101@lpu.co.in)